

# HARDWOOD STARTING STEPS

Check local building code requirements before specifying any starting step.



Starting steps are shipped complete with the starting riser, starting tread, and all cove and shoe moulding.

Starting risers are available in a selection of hardwood species or paint-grade poplar.

Separate Cove Moulding Sets and Shoe Moulding Sets are available in all starting step profiles. *Example: C-8010 Cove and C-8010 Shoe.*

**NOTE:** Please specify right or left hand when ordering single end starting steps. Reversible starting steps are available as an option.

When measuring for finished stair width on double end starting steps, include all finish materials. *Example: Sheetrock, skirtboard, decorative tread brackets, etc.*

**C-8010 Bullnose**  
Usable with all turnouts and volutes.

**C-8015**  
Usable with all turnouts and volutes.

**C-8020 Scroll End**  
Usable with all turnouts and volutes.

**C-8025**  
Usable with all turnouts and volutes.

| Order Item | For finished stair width of |
|------------|-----------------------------|
| C-8016-48  | 43" to 48"                  |
| C-8016-53  | 48" to 53"                  |
| C-8016-58  | 53" to 58"                  |

**C-8016 Adjustable Double End Bullnose**  
Usable with all turnouts and volutes. Three adjustable sizes allow job site trimming for exact finished fit.

| Order Item | For finished stair width of |
|------------|-----------------------------|
| C-8065-48  | 43" to 48"                  |
| C-8065-53  | 48" to 53"                  |
| C-8065-58  | 53" to 58"                  |

**C-8065 Adjustable Bowed Starting Step**  
Usable with all turnouts and volutes. Three adjustable sizes allow job site trimming for exact finished fit.

**C-8040 Quarter Circle**  
Usable in stair designs that require a flush mounted starting step.

**C-8060**  
Usable in stair designs that require a flush mounted starting step.

**C-8041 Quarter Circle**  
Usable in stair designs that require a flush mounted step with starting fittings.

**C-8061**  
Usable in stair designs that require a flush mounted step with starting fittings.

**C-8030 Half Circle**  
Use with C-7133/C-7138 Ascending Volute, and usable with larger profile volutes, ascending volutes, PTP systems and box newels.

**C-8050**  
Use with C-7133/C-7138 Ascending Volute, and usable with larger profile volutes, ascending volutes, PTP systems and box newels.

**C-8630 Half Circle**  
Usable with larger profile volutes and ascending volutes, PTP systems and box newels.

**C-8650**  
Usable with larger profile volutes and ascending volutes, PTP systems and box newels.